



TARDIS MANUFACTURING CC t/a

Advanced Cement

Manufacturers of elegant cemented wall & floor concepts

Product Sheet – Venetian Plaster

Description

Venetian Plaster is a decorative trowel-on acrylic coating with an interesting veined, smooth textured and glossy look. It is a natural product composed of organic ingredients, limestone, and acrylic binders, formulated to create an authentic old world look and feel of stone, while giving you a washable, breathable, non-toxic, low VOC, and ecological green luxurious finish.

Preparation

All surfaces should be dry, clean, firm and free from dust, oil, grease, rust and powdery or flaking paint. Apply one coat of Plaster Primer to prevent sliding. Surfaces should be fairly even as the coating is applied thinly and does not have a high build.

Application

Apply a coat of Venetian Plaster with a steel trowel or scraper, keeping a consistent pattern to the applied coating. Coat approximately 3 square metres at a time to avoid the first area to harden. Continue in the same manner, keeping a wet edge until the whole wall is covered. Do not stop in the middle of a wall, go from corner to corner. Allow to dry overnight and sand lightly with P120 sandpaper.

Apply the second coat thinly with a trowel. There should be some high points of the first coat exposed as this coat is applied. Allow to dry overnight and sand lightly with P320 sandpaper. On bigger areas an orbital sander can be used.

Apply two coats of Cobra wax or Floor Revive to achieve an even sheen on the whole surface.

Spreadrate

Approximately 1.5 square metres per litre per coat, depending on roughness of substrate and thickness of application. Due to the variance in different surfaces, spreadrates cannot be guaranteed. It is advised that a test site application be done to determine effective coverage. If Venetian Plaster is applied too thick, the product may crack.

Cleaning Clean all equipment with water

Dilution Not recommended

Reg Nr: 2014/197853/07	Vat Nr: Pending
Honeydew Shopping Centre Unit 59, 1 Blueberry Street, Honeydew	
Unit 7, Pryde Business Park, Broadlands Road, Somerset West	
P O Box 230, Honeydew, 2040 email: info@advancedcement.co.za	
Tel: 011 794 2403	Fax: 086 619 3926